



www.litprints.co.uk

Contents:



x4 Truss



x1 Handrails



x4 Leg Base



X6 Wire Cover




x4 Leg top





X2 Legs and x1 ladders







## **Dear Customer**

Thank you for your purchase and interest in our OO Gauge 5-6 Track Signal Gantry kit.


It has been designed to fit together with glue and to be wired for animated look.

This is a UK Type aspect signal that covers up to 6 tracks.

Tools required: glue, soldering iron, solder



- 1) First prepare the LEDs for soldering and cabling. Use 3 cables for the 2-light system and 4 cables for the 3-light system.
- 2) Join the negative prongs to one cable for each set of LEDS, then solder a cable to all the positive Prongs individually. Note: the long prong on the LED is positive. (3-5V only)



- 3) Once LEDS and cables have been soldered, Slot them into the ASP hoods in the order like the images above.
- 4) Fold each rail up and glue the handrails together: use a ruler along the folding seems to assist.









5) Glue the parts together as shown on the right. Make sure the smooth backs of the legs are facing inwards.

(Parts needed: Legs, leg base and leg top)

- 6). Prepare truss sections. It is possible to cut down the truss length to match your designed track length.

Glue truss parts to Truss mounts as shown. Add legs as shown. Keep orientation as shown in image D and E so the wire feed






Α







8) Glue the ASP hoods into locations as shown in the image above on the right. Feed wires along one side of the walkway and into the wire runs down the leg. Add cable cover as shown below in A, then glue final 2 parts of the gantry into place as shown in B.



9) Lastly glue the ladder and as show above in image C. Add the number plate to one of the legs as seen in image D. You can also add the Overhead line equipment to any track that requires it. Once complete wire this up to your chosen controller.